Application No.: 10/539,010

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

1. (canceled).

2. (currently amended): A cassette relay block attachment structure comprising:
a cassette relay block having a lock portion disposed inwardly of an outermost wall
surface of the cassette relay block, the cassette relay block being inserted into a space surrounded
by peripheral walls on an attaching member, said cassette relay block being fixed by the lock
portion and a locked portion located on the peripheral wall side of the attaching member; The
cassette relay block attachment structure according to Claim 1,

wherein said lock portion and locked portion are housed in the projected area of a relay attached to said cassette relay block.

3. (currently amended): A cassette relay block attachment structure comprising:
a cassette relay block having a lock portion disposed inwardly of an outermost wall
surface of the cassette relay block, the cassette relay block being inserted into a space surrounded
by peripheral walls on an attaching member, said cassette relay block being fixed by the lock
portion and a locked portion located on the peripheral wall side of the attaching member; The
cassette relay block attachment structure according to Claim 1,

wherein terminal housing parts of said cassette relay block are arranged crosswise, and said lock portion is arranged in a range surrounded by crossing outer wall surfaces of the terminal housing parts.

4. (currently amended): The cassette relay block attachment structure according to Claim 42, characterized in that said lock portion is a flexible lock arm.

Application No.: 10/539,010

5. (currently amended): The cassette relay block attachment structure according to

Claim <u>42</u>, further comprising:

a rib provided on the opposite side to said lock portion side and for one of said cassette

relay block and said peripheral walls; and

a guide groove for slide engagement with the rib provided for the other.

6. (currently amended): The cassette relay block attachment structure according to

Claim 42, wherein said peripheral walls on the attaching member are formed as a cassette frame.

7. (original): The cassette relay block attachment structure according to Claim 6,

wherein said cassette frame serves as one of said cassette relay block and other cassette electric

parts mounting blocks.

8. (previously presented): The cassette relay block attachment structure according to

Claim 6, wherein the inner surfaces of said peripheral walls are housed in the projected area of

said relay.

9. (previously presented): The cassette relay block attachment structure according to

Claim 6, wherein the cassette frames having lock members, respectively, are coupled to each

other by the lock members, and the cassette frames are coupled to a connection box body having

locked members to constitute an electric connection box.

10. (previously presented): The cassette relay block attachment structure according to

Claim 2, wherein terminal housing parts of said cassette relay block are arranged crosswise, and

said lock portion is arranged in a range surrounded by crossing outer wall surfaces of the

terminal housing parts.

11. (previously presented): The cassette relay block attachment structure according to

Claim 2, characterized in that said lock portion is a flexible lock arm.

3

Application No.: 10/539,010

12. (previously presented): The cassette relay block attachment structure according to Claim 3, characterized in that said lock portion is a flexible lock arm.

- 13. (previously presented): The cassette relay block attachment structure according to Claim 2, further comprising:
- a rib provided on the opposite side to said lock portion side and for one of said cassette relay block and said peripheral walls; and
  - a guide groove for slide engagement with the rib provided for the other.
- 14. (previously presented): The cassette relay block attachment structure according to Claim 3, further comprising:
- a rib provided on the opposite side to said lock portion side and for one of said cassette relay block and said peripheral walls; and
  - a guide groove for slide engagement with the rib provided for the other.
- 15. (previously presented): The cassette relay block attachment structure according to Claim 4, further comprising:
- a rib provided on the opposite side to said lock portion side and for one of said cassette relay block and said peripheral walls; and
  - a guide groove for slide engagement with the rib provided for the other.
- 16. (previously presented): The cassette relay block attachment structure according to Claim 2, wherein said peripheral walls on the attaching member are formed as a cassette frame.
- 17. (previously presented): The cassette relay block attachment structure according to Claim 3, wherein said peripheral walls on the attaching member are formed as a cassette frame.
- 18. (previously presented): The cassette relay block attachment structure according to Claim 4, wherein said peripheral walls on the attaching member are formed as a cassette frame.

Application No.: 10/539,010

19. (previously presented): The cassette relay block attachment structure according to

Claim 5, wherein said peripheral walls on the attaching member are formed as a cassette frame.

20. (previously presented): The cassette relay block attachment structure according to

Claim 7, wherein the inner surfaces of said peripheral walls are housed in the projected area of

said relay.

21. (previously presented): The cassette relay block attachment structure according to

Claim 7, wherein the cassette frames having lock members, respectively, are coupled to each

other by the lock members, and the cassette frames are coupled to a connection box body having

locked members to constitute an electric connection box.

22. (previously presented): The cassette relay block attachment structure according to

Claim 8, wherein the cassette frames having lock members, respectively, are coupled to each

other by the lock members, and the cassette frames are coupled to a connection box body having

locked members to constitute an electric connection box.

5